

PRODUCT COMPARISON GUIDE FLEXIBLE FLOOR BUNDING



50mm LOW PROFILE



75mm MEDIUM PROFILE



150mm HIGH PROFILE

HEIGHT	RISK LEVEL	BEST FOR	DRIVE OVER STABILITY	TYPICAL APPLICATIONS	COMPATIBLE PRODUCTS
50mm Low Profile	Low Risk	<p>Simple containment lines with easy movement of people and equipment.</p> <p>Ideal where spills are infrequent and volumes are small.</p>	Occasional low speed crossings where clearance allows.	<ul style="list-style-type: none"> Walkways Door thresholds Mixed use areas Light interaction zones 	<ul style="list-style-type: none"> 2mL Bunding (50 mm) 90° Corner Join (50 mm) Install Kit: 2mL Install Kit: 90° Corner
75mm Medium Profile	Medium Risk	<p>A balance of containment height + drive-over capability.</p> <p>Suitable for areas with moderate spill risk and regular equipment use.</p>	Most drive over friendly option for forklifts and pallet jacks at low speed.	<ul style="list-style-type: none"> Operational bays Transfer points Maintenance zones Shared access areas 	<ul style="list-style-type: none"> 5mL, 10mL, 30mL Bunding (75 mm) 90° Corner Join (75 mm) Install Kits: 5mL, 10mL
150mm High Profile	High Risk	<p>High-volume containment where preventing liquid escape is critical.</p> <p>Best for dedicated containment areas. Not suitable for drive-over.</p>	Not intended for drive over.	<ul style="list-style-type: none"> Chemical storage Plant rooms Generator Battery rooms Bunded perimeters where traffic can be rerouted 	<ul style="list-style-type: none"> 2mL Bunding (150 mm) 90° Corner Join (150 mm) Install Kit: Matching size