



- ✓ Easy clean surface
- ✓ High UV resistance
- ✓ Self-extinguishing fire-retardant properties



## VEHICLE WASH MATS

CAPTURE WASTE WATER DURING WASHDOWN ACTIVITIES

Wash Mat	Code	Length	Width	Height	Capacity
Car	CHWM02	6m	3m	75mm	1,350L
Car	CHGM02	7m	4m		
Truck	CHWM01	18m	4m	75mm	5,400L
Truck	CHGM01	19m	5m		



Vehicle Wash Mats, available in standard dimensions for cars or trucks, feature bund walls with continuous foam sides. This construction allows for resilience against both vehicular traffic and foot traffic, ensuring durability and versatility.

Placing a Ground Mat beneath a soft material provides protection against punctures and abrasions. The geotextile material permits water to pass through, preventing water pooling.

For best results a Vehicle Wash Mat should be used with a geotextile underlay to prevent damage to the mat. If the use of an underlay is not possible, the mat can be manufactured using reinforced polypropylene fabric for extra durability.

### APPLICATION EXAMPLES:

- Portable motor vehicle washing
- Permanent wash bays
- Truck and machinery wash down
- Temporary containment of leaking equipment
- General spill containment bund

### OPTIONS

- Custom Sizes Available
- Upgrade to Heavy Duty Geomembrane for durability and increased chemical resistance
- Ground Mat to increase longevity and protect against punctures on rough surfaces

### SPECIFICATIONS:

- Foam bund wall height of 75mm
- Heavy duty 900gsm PVC
- Acceptable temperature range of -20 to +70°C

