CHATOYER

SPILL CONTAINMENT

Flexible Floor Bunding 75 mm

A 75 mm triangular bund wall that compresses under low-speed forklift traffic and returns to shape.

HEIGHT
75 mm

SECTION LENGTH
2 m

MATERIAL
900 gsm hi-vis PVC



THE RANGE

Code	Description
CHFFB01	SpilMax Flexible Floor Bunding (10mL x 205mmW x 75mmH)
CHFFB02	SpilMax Flexible Floor Bunding (30mL x 205mmW x 75mmH)
CHFFB03	SpilMax Flexible Floor Bunding (5mL x 205mmW x 75mmH)
CHFFB08	SpilMax Flexible Floor Bunding Installation Kit for 90° Corner Join KIT
CHFFB29	SpilMax Flexible Floor Bunding 90° Corner Join (300mmL x 205mmW x 75mmH)
CHFFB36	SpilMax Flexible Floor Bunding Installation Kit for 5mL KIT
CHFFB37	SpilMax Flexible Floor Bunding Installation Kit for 10mL KIT
CHFFB44	SpilMax Flexible Floor Bunding Installation Kit for 30mL KIT

BEST FIT FOR

- ✓ Low speed forklift crossings into bunded work bays and maintenance zones
- ✓ Transfer or decanting points where you want more containment height without blocking access
- ✓ Warehouse operational areas where a visible boundary helps keep spills in zone

Specifications	
Material type	Heavy Duty Hi-Vis PVC
Material weight	900 gsm
Chemical resistant	Yes